
Configuration Sheet Internal fitting kit (K3.11) layout



LAYOUT



© 2020 Ergrownomics Limited

Specification Sheet

Internal fitting kit (K3.11) contents



| PLANTERS | Unit |
|--|------|
| Three Planter (frame only) | 1 |
| Four Planter (frame only) | 2 |
| Horticultural container (577 mm (l) x 588 mm (w) x 385 mm (d) internal dimensions) (85 litre soil capacity) | 11 |
| Hexagonal key ('L' shaped 1/4" ductile carbon steel to DIN 11 with precision square cut ends for accurate contact to hex plug wall sides) | 1 |
| DRAINAGE | |
| Thermally bonded non woven geotextile membrane (110 grams m2) (510 mm (l) x 425 mm (w)) (0.22 m2) for lining base of container / protecting 'bean bag' | 11 |
| Heavy duty PVC mesh bag (550 grams m2) (570 mm (l) x 280 mm (w) (0.16 m2) (gravel not supplied) | 11 |

| IRRIGATION | |
|--|-----|
| Lock Type fitting quick coupling - threaded elbow, 16 mm (external diameter) | 1 |
| Lock Type fitting quick coupling - threaded tee, 16 mm (external diameter) | 5 |
| Standard length pipe interconnector to fittings along irrigation manifold (67 mm) Medium duty Rain Bird LDPE 16mm solid black irrigation pipe (4 bar) | 3 |
| Medium duty Rain Bird LDPE 16mm solid black irrigation pipe (4 bar) for multiple rows of planter units. (To be cut to length in situ) (m) | 3.0 |
| Triple length (1980 mm) Rain Bird XF Series dripline 16 mm (external diameter) with emitters at 33 cm centres (2.3l/hr flow rate) for three horticultural containers | 2 |
| Quad length (2680 mm) Rain Bird XF Series dripline 16 mm (external diameter) with emitters at 33 cm centres (2.3l/hr flow rate) for four horticultural containers | 4 |
| Barbed plug 16 mm (external diameter) / 13.6 mm (internal diameter) | 6 |
| Atelco 16 mm tubing clamp with ratchet closure to secure dripline over plug) | б |
| Garden 3/4 BSPF Tap Connector Male Brass QC | 1 |

PLANT TRAINING

| Adjustable support (aluminium) (12 mm diameter x 360 mm length) | 2 |
|---|---|
| Vinyl stop end to adjustable support to provide eye protection (10 mm x 25.40 mm S-Cap) | 2 |
| Rubber-'O' ring (BS309 EPDM 70 ShA) | 2 |
| Elastic supporting lines (1,240 mm length x 3.0 mm diameter) with short brass aglets fitted | 1 |
| Spherical cord lock black nylon for 3-4 mm diameter cord | 1 |

Please note that this product specification is subject to change at the manufacturer's discretion.